

NIPPON KAIJI KYOKAI

Approval No. NKY-3010 Certificate No. TA20864E Certificate TYPE APPROVAL

Article:

Welding Consumables for High Tensile Steel used to

Low Temperature Service

Brand:

DW-55LSR

Applicant:

Kobelco Welding of Korea Co., Ltd.

Changwon, Gyeongnam, Korea

Manufacturer:

Kobelco Welding of Korea Co., Ltd.

Changwon, Gyeongnam, Korea

Grade:

Manufacturer's Specification (Equivalent to KSW5Y42G(C) H5)

Welding Process:

Welding Positions and Max. Diameter of Wire: See Table 1

Semi-Automatic Welding (MAG Welding)

Current:

DCEP

Shielding Gas:

 CO_2

Remark:

Mechanical properties are to comply with the requirements specified in

Table 2 and Table 3.

Table 1 Welding Positions and Max. Diameter of Wire

Butt Weld		Fillet Weld		
Flat:	1.2mm	Flat:	1.2mm	
		Horizontal Vertical:	1.2mm	
Horizontal:	1.2mm	Horizontal:	1.2mm	
Overhead:	1.2mm	Horizontal Overhead:	1.2mm	
		Overhead:	1.2mm	
Vertical Upward:	1.2mm	Vertical Upward:	1.2mm	
Vertical Downward:	1.2mm	Vertical Downward:	1.2mm	

THIS IS TO CERTIFY that the above mentioned welding consumable has been approved by the NIPPON KAIJI KYOKAI in accordance with the requirements of the Society's Rules.

This Certificate will remain in force until 12 June 2021. Issued at Tokyo on 28 May 2020.

Y. Takao

General Manager

Material and Equipment Department

Note: (1) The validity of this certificate may be renewed by endorsement on the attached sheet upon completion of the annual inspections.

(2) This certificate was rewritten because of change of the applicant's name and the manufacturer's name.

Table 2 Mechanical properties (as welded)

Deposited Metal Test			Butt Weld Test		
	Tensile Te	est	Impact Test	Tensile test	Impact Test
Tensile strength (N/mm²)	Yield point (N/mm²)	Elongation (%)	Testing temperature (°C) and Minimum mean absorbed energy (J)	Tensile strength (N/mm²)	Testing temperature (℃) and Minimum mean absorbed energy (J)
530 \sim 680	420 min.	20 min.	47J at -60℃ or 27J at -68℃	530 min.	47J at -60℃ or 27J at -68℃

Table 3 Mechanical properties (SR($575^{\circ}C \times 1$ hour))

Table 6 Mediamear properties (Str(676 C × modr))					
Deposited Metal Test			Butt Weld Test		
Tensile Test Impact Test		Tensile test	Impact Test		
Tensile strength (N/mm²)	Yield point (N/mm²)	Elongation (%)	Testing temperature (°C) and Minimum mean absorbed energy (J)	Tensile strength (N/mm²)	Testing temperature (°C) and Minimum mean absorbed energy (J)
530 ~ 680	420 min.	20 min.	47J at -60°C	530 min.	47J at -60℃

The validity of this certificate has been renewed	The validity of this certificate has been renewed		
until 2022 .06. 12 .	until		
Date: 2021 .03, 31 Surveyor	Date:		
The validity of this certificate has been renewed	The validity of this certificate has been renewed		
until 2023.66.12.	until		
Date: 2022.05.26	Date:		
Surveyor	Surveyor		
The validity of this certificate has been renewed	The validity of this certificate has been renewed		
until 2024, 06.12.	until		
Date: 2023 ,06, 08	Date:		
Surveyor	Surveyor		
The validity of this certificate has been renewed	The validity of this certificate has been renewed		
until 2025, 06, 12.	until		
Date: 2014 0523	Date:		
Surveyor	Surveyor		
The validity of this certificate has been renewed	The validity of this certificate has been renewed		
until	until		
Date:			
	Date:		